



TOWING HEADS

The Pipe Equipment range of Towing Heads offer a quick, simple and reliable method of attaching a winch wire, pipe burster, or other pulling device, to a plastic pipe. All styles are manufactured from high quality materials and have undergone comprehensive tests to ensure they are suitable for their application. They are manufactured to suit both metric and imperial pipe sizes. An extensive stock of Towing Heads is maintained, with items available both for purchase and hire.



◀ STANDARD TOWING HEAD

Applications: General pipe pulling operations such as slip lining and pipe uncoiling.

Size Range: 20mm up to 630mm



◀ PRESSURE TIGHT TOWING HEAD

Applications: Installation of pipes that need to be pressure tested, or installation of pre-chlorinated pipes.

Size Range: 25mm up to 500mm



◀ MUD TIGHT TOWING HEAD

Applications: Directional Drilling

Size Range: 32mm up to 500mm



◀ PE TOWING HEAD

Applications: Directional Drilling, Slip Lining and Direct Burial.

Size Range: 200mm up to 630mm



◀ BOLT ON TOWING HEAD - Standard or Fully Sealed

Applications: For PE sizes 400mm +
Standard for slip lining / Sealed for Directional Drilling

Size Range: 400mm +

**For more detailed information on any of the above
please refer to our product literature sheets**

The company follow a policy of continuous product development and as such reserves the right to make alterations to equipment and techniques without prior notice.

PIPE EQUIPMENT SPECIALISTS LTD

66 DUKESWAY, TEESIDE INDUSTRIAL ESTATE, THORNABY, STOCKTON-ON-TEES, TS17 9LT, ENGLAND

TEL: +44 (0) 1642 769789 FAX: +44 (0) 1642 769456

www.pipe-equipment.co.uk Email: info@pipe-equipment.co.uk



Certificate Number: 1253

WP/TH/204